



# LIDS & OVERCAPS



## ROUND AND NON-ROUND OVERCAPS FOR COMPOSITE CANS, METAL CANS, PAPERBOARD CUPS, AND INJECTION MOLDED AND THERMOFORMED CONTAINERS

IPL manufactures the industry's highest quality lids and overcaps for many leading brands in the food industry.

### CERTIFICATIONS

The raw materials used are tested according to ASTM standards for polymers, are approved for food contact and meet FDA (Food and Drug Administration, USA) and HPB (Health Protection Branch, Canada) regulations.



IMS

### MINIMUM ORDERS AND INFORMATION

For details on minimum order quantities or for any other additional information, please contact IPL customer care at 1-800-647-0602 or visit our web site at [www.ipl-plastics.com](http://www.ipl-plastics.com).

### RECOMMENDATIONS

Handling conditions vary from customer to customer. We recommend validating your processes (filling, conveying, warehousing and any others that might affect the purchased part) prior to use. Product usage temperature is between -9.4°F (-23°C) and 179.6°F (82°C) depending on resin grade.

### APPLICATIONS

- Beer and beverages
- Drink mixes
- Infant Formula
- Coffee
- Snacks
- Dried fruits
- Dips
- Soups
- Bread crumbs
- Cereals
- Ice Cream

### MATERIALS

Lids are made of recyclable polypropylene (PP) and linear low-density polyethylene (LLDPE).



### TRADITIONAL DECORATION OPTIONS

- Dry offset printing
- Pressure-Sensitive Labeling (PSL)

### CUSTOM DECORATION OPTIONS

- Engraving / Embossing
- In Mold Labeling (IML)
  - Traditional
  - Paperboard Insert

### COLOR CODE

BASE COLORS	STANDARD COLORS	OTHER COLORS
Natural	Yellow 05	Available upon request**
White 03	Blue 96	
Clear *	Blue 04	
	Black 05	

\* Where clarified polypropylene is used

\*\* IPL processes several different colors and has color matching capabilities as well.



Our lids are reusable and 100% recyclable because at IPL, we care about the environment.





### LIDS

PRODUCT CODE	APPROX. WEIGHT (g)	INSIDE DIAMETER (in.)	ITEMS PER BOX	BOXES PER PALLET	ITEMS PER PALLET
<b>COMPOSITE CAN OVERCAP SERIES</b>					
211CE	2.9	2.714	2,604	30	78,120
301A	4.3	3.070	1,960	25	49,000
301CE	3.6	3.013	1,125	45	50,625
307CE	4.9	3.434	2,160	16	34,560
401CE	6.3	4.048	1,500	24	36,000
402CF	6.5	4.098	1,225	28	34,300
402CF PP clarified	5.1	4.086	1,225	28	34,300
502CC	11.0	5.126	840	24	20,160
603CE	15.8	6.217	594	20	11,880
<b>PAPERBOARD CONTAINER OVERCAP SERIES</b>					
300UK	4.3	3.148	1,400	20	28,000
307SS	5.3	3.554	1,680	16	26,880
308	5.6	3.507	1,750	16	28,000
314UK	6.0	3.892	1,500	20	30,000
401UK	7.2	4.203	840	20	16,800
504	11.5	5.277	944	16	15,104
NR500	9.6	5.220 X 4.003	600	30	18,000
NR680	10	5.380 X 4.160	600	30	18,000
912	52.5	9.707	100	24	2,400
<b>PLASTIC CONTAINER OVERCAP SERIES</b>					
402P	6.4	4.111	1,120	25	28,000
408	7.5	4.491	696	30	20,880
409PP	5.8	4.550	1,200	25	30,000
409PP Clarified	5.8	4.555	1,200	25	30,000
514	15.0	5.880	480	20	9,600
514IN	10.6	5.875	888	20	17,760
<b>METAL CAN OVERCAP SERIES</b>					
307	4.6	3.386	2,520	20	50,400
401	6.0	3.976	1,500	24	36,000
502	10.0	5.063	1,000	24	24,000
603	15.3	6.138	405	24	9,720
<b>KEG OVERCAP SERIES</b>					
208	2.9	2.506	2,000	42	84,000

### WARRANTIES

- Some chemicals can affect the integrity of the product. Any product requiring a Safety Data Sheet (SDS) has to be submitted and approved by IPL. If buyer fails to adhere to this clause, the related product guarantees will be void.
- Specifications may vary slightly over time. Please contact your IPL representative to ensure you have the most recent information.
- The information presented herein was prepared at IPL Inc. by qualified technical personnel. To IPL's knowledge, it is true and accurate. However, the information and recommendations are provided for these products with the understanding that the purchaser or user will independently determine that the product is suitable for the intended use, and that such use, complies with all applicable laws and regulations. The data represents typical values submitted only for the user's information and consideration and does not constitute a warranty of any kind.

